

Tough! Toyota Land Cruiser 4-wheel Drive Built to take it... And take you where you want to go

Point its nose for the way-back country. Out where the pavement ends. Enjoy the adventure of offroading. Plough through sand, mud, rocks, snow, ice-the Toyota Land Cruiser with 4-wheel drive flattens out the steepest hills, gets you there when others get hung up. Gutsy 6-cylinder 155 HP powerplant, fabulous gear combinations of six forward speeds and two reverse, brawny chassis and heavy duty axles, rugged body with vinyl top, all designed to make this versatile vehicle an outstanding performer at all sorts of jobs: construction, forestry, engineering, surveying and exploring. As a recreational vehicle or reliable workhorse, you'll find the Toyota Land Cruiser's unsurpassed. That's why it's so popular all over the world!







It's tough, agile, yet still well-mannered, with a husky 6-cylinder 155HP engine that makes tackling the toughest jobs easy. This Hardtop takes the worst roads, the most impossible conditions in stride. Equally at home getting in to inaccessible construction sites or on weekend family outings or vacation camping trips, it's an ideal combination of brawny body construction, brute power, 4-wheel drive, comfort and safety features. What more could you want? Swing-out type rear door is available

as an option.









Except for the top material, the Toyota Land Cruiser Hardtop and Vinyl Top are basically the same. However, a larger version is available in the Vinyl Top model (FJ43) with a longer wheelbase (2430 mm. or 95.7in.), a longer body (4230 mm. or 166.5 in.) and bigger interior dimensions. The Vinyl Top's extremely easy to take off and stow so you can enjoy the fun of topless driving when the weather's right. Room for seven passengers to ride in comfort and safety on vinyl upholstered seats. The instrument panel is designed for ease of operation; all control buttons are picture-symbol identified.

And its outstanding durability insures that this vehicle will last for years and years. Optional top-hinged windscreen (pushopen type) can be opened from the bottom.





Convenient in size with the power, stamina and utility to outdo anything in its class: that's the Toyota Land Cruiser Pickup. With a husky 6-cylinder 155 HP engine teamed up with 4-wheel drive, it'll carry loads in and out of places other pickups can't go. A large, solid, heavy duty cargo deck lets you haul pipes, logs, lumber, stands up to the worst punishment indefinitely. Why not put a Toyota Land Cruiser Pickup to work and discover its unequalled capabilities.

Interior dimensions of cargo deck: Length, 2135 mm. (84.1in.); Width, 1590 mm. (62.6 in.); Height, 415 mm. (16.3 in.). Rooftop, doors and rear guard frame are detachable.


The comfort and luxury of a family fun car plus the toughness and durability of a commercial vehicle give this one a dual personality. The Toyota Land Cruiser Station Wagon does so many things so well you'll wonder how you ever got along without it. A powerful 6-cylinder 155 HP engine lets this Wagon keep up with anything on the road or off it. Spacious cargo area with flat floor and wide opening tailgate makes loading/ unloading easier for business or pleasure.

Some outstanding interior features:

- (1) Easy-to-operate instrumentation designed for safety (radio, heater, defroster optional)
- (2) Vinyl upholstered front seats—complete with seatbelt anchorages.









The Land Cruiser Station Wagon's rear window (drop-down type rear gate) can be lowered or raised by flicking a dash switch. A nice little extra at no extra cost.



Station Wagonr ga









gonr gate: drop-down type)

Station Wagon (Rear gates: swing-out type)

Dual speed wiper/ washer (option) with glareproof arms. Front side turn signal. High intensity light makes it easy to see. h Hood opens extra wide for easy engine aı access. Inside rear view ea he mirror, breaks away on impact. Sun visor (standard equipment) except co-driver's sun visor Air outlet (engine 10 (option). room). 10 10 Mo dri driv Assist grip mounted me above glove Front winch control lever (option). compartment. Ins fea kno Pic High efficiency heater Har (option). leat Tra and ope on Fro Head-rest (option). and Sta FJ oth Fro upr ang opi Arrangement of SeatsFloor trar and on t Har Hardtop (FJ40V) com Vinyl Top (FJ40) doo ran case Opt win зуре Reversing light. Vinyl Top (FJ43) Vin Cato win Tail light, Brake light & Rear turn signal. Reflector. Bumper.

The and Cruiser eatures all hese and more

lore comfort, lore versatility, lore options.


Model with floorinted shift/4-wheel drive lever. Four wheel drive may be disengaged merely by pulling a knob. Instrument panel features; easy-to-operate knobs and switches; Picture-identified knobs. Handsome vinyl leatherette seats; Transfer-case shift lever and 4-wheel drive operating lever, mounted on the centre floor. Front seat adjusts fore and aft 140 mm. (5.5 in.). Standard on FJ55V and FJ45PB, optional on other models. Front seatbacks lock upright for safety and angle of seatback can be ated. Seat belts are optional. eatsFloor mounted 3-speed transmission shift lever and 4-wheel drive lever on the right. Handy glove

compartment. Plate on door explains use of transmission, transfer case, 4-wheel drive, etc. Optional top-hinged windscreen (push-open type) can be opened from the bottom

Vinyl Top models only). Catches for tilting windscreen.

























Rear seats (Hardtop model).

Steering worm & sector roller type.
Collapsible steering column with steering lock (option; Station Wagon R.H.D. only).

Radiator.

Ur

to

or ev

Cal D D La

> 15 31 of

Thre

dr

er

pc ve 32-


ge di ra co th th

A

an sy Fr W СО the ell do ab СО Fr flo dri Re se sp an co an Po pu

op

Tyre type: Ribbed, Semi-lug, Grip,/ Snow*, Sand.* (*Snow and Sand tyres are optional.)





Differential gear (rear).


Under its tough exterior lurks a tough heart

Rugged, powerful, ong-lasting... every component can take it.

- Durable engine: Toyota Land Cruiser 4-wheel drive is equipped with a husky 6-cylinder OHV, 3978 c.c. (236.7 cu.in.) ne that develops 155 HP at 4000 rpm and 31.7 m/kg. (230 ft.lbs.) of torque at 2200 rpm. This high output at slow revs. means greater driving comfort and longer engine life. The engine is equipped with positive crankcase ventilation system.
- 2-speed transfer case combined with 3-speed gearbox provides 6 different gear speed ratios. This ideal combination will take the Land Cruiser through the worst conditions or terrain.
- Alternator 12-volt 480 watt alternator.
- erful brake booster and double circuit brake system (option).
- Front suspension: 4wheel drive and steering components withstand the roughest use. Semielliptic leaf springs and double-acting shock absorbers give maximum comfort.
- Front axle is fullfloating hypoid gear drive type.
- Rear axle is durable, semi-floating type. Leaf springs, shocks and antiroll bar ensure a safe, comfortable ride over any surface.
- Powerful winch for any pulling or lifting needs is optional equipment.






















SPECIFICATIONS

Engine: 6-cylinder in line, OHV, 3,878 c.c. (236.7cu.in.). Bore, 90 mm (3.54in.). Stroke, 101.6 mm (4.00 in.). Compression ratio, 7.8 to 1. Maximum horsepower, 155 HP (SAE) at 4.000 rpm. Maximum torque, 31.7 m-kg (230ft-lb) (SAE) at 2,200 rpm. 12-volt 50 amp.hr. battery. 12-volt 480 watt alternator. Down-draft 2-barrel carburettor with automatic choke. Fuel tank capacity; 70 litres (15.4 Imp.gal.), Station Wagon, 90 litres (19.8 Imp.gal.). Cooling system; Forced circulation by centirifugal pump. Lubrication system; Forced lubrication by gear pump. Water capacity; 15.2 litres (13.4 lmp.qts.). Engine oil capacity; 8.5 litres (7.5 lmp.qts.). Clutch: Dry single plate with torsion rubbers. Facing diameter, 275 mm (10.8 in.). Facing area, 716 sq.cm. (111.0 sq.in.).

Transmission: 3-speed, 2nd and 3rd gear synchromesh. Gear ratios; 1st, 2.757; 2nd, 1,691; 3rd, 1.000; Reverse, 3.676. Shift lever mounted centre floor.

Transfer: 2-speed helical gear sliding type. Ratio; Low, 2.31, High, 1.00.

Front axle: Full-floating, hypoid gear drive. Ratio; 3.70 (4.11 for FJ45PB).

Suspension: Front and rear; Semi-elliptic leaf springs and double-acting hydraulic telescopic shock absorbers

Brakes: Hydraulic brakes operate on all wheels. Drum diameter; 290 mm (11.4 in.). Lining area; 1,180 sq.cm. (182.9 sq.in.). Parking brake: Mechanical brake operates on propeller shaft.

Steering: Worm and sector roller type. Gear ratio; 21:1.

Performance: Maximum speed; 125 km/h (80 mph.).

MAJOR ITEMS OF **OPTIONAL EQUIPMENT**

☐ Starting handle (not available w/front winch, std. on FJ55V) ☐ Steel doors (for Vinyl Top model) □ Wheel caps (std. on FJ55V) □ Semistake and canvas hood for deck (for FJ45PB) □ Various Types of rear door on Vinyl Top

□ Inlet fuel strainer □ Fuel tank lock (std. on FJ55V) □ Spare fuel tank □ Pintle hook (except FJ45PB) Trailer socket (except FJ45PB) Body undercoating (std. on FJ55V) ☐ Heater/defroster □Windscreen washer □Alternator 480 W (low rev. charging) or 660 W □ Collapsible steering Column with steering lock (opt. on FJ55 RHD only) Seat adjuster (std. on FJ55V, FJ45PB) ☐ Front seat head restraints ☐ Additional parallel or transverse type rear seat □ Seatbelts □ Floor mat (std. on FJ55V) ☐ Fog lamps ☐ Hazard warning light switch ☐ Folding front windscreen (for FJ40, FJ43) □Chrome bumper & grille □ Radio & antenna □ Short wave adapter ☐ Cigarette lighter ☐ Variations in tyre size and tread type ☐ Front-mounted winch ☐ Hi-power battery (12 V., 70 amp.hr.) Differential with gear ratio 4.11 (std. on FJ45PB) □ Brake booster (FJ40, FJ55 only) 4-speed floor shift type gearbox (full synchro) with two, speed transfer (FJ45PB, FJ55V only) Air conditioner (Optional on FJ55V only)

Station Wagon Pickup Hardtop Vinyl Top

imensions		Vinyl Top (FJ40)	Hardtop (FJ40V)	Vinyl Top (FJ43)	Pickup (FJ45P-B)	Station Wagon (FJ55V)
Wheelbase mm (in.)		2,285 (90.0)		2,430 (95.7)	2,950 (116.1)	2,700 (106.3)
front	mm (in.)	1,404 (55.3)		1,404 (55.3)	1,404 (55.3)	1,405 (55.3)
Tread, rear		1,400 (55.1)		1,400 (55.1)	1,400 (55.1)	1,400 (55.1)
length	mm (in.)	3,870 (152.4)		4,230 (166.5)	4,985 (196.3)	4,675 (184.0)
width	mm (in.)	1,665 (65.6)		1,665 (65.6)	1,690 (66.5)	1,735 (6
height	mm (in.)	1,950 (76.8)	1,930 (76.0)	1,970 (77.6)	1,960 (77.2)	1,865 (73.4)
Ground clearance mm (in.)		200 (7.9)		210 (8.3)	230 (9.1)	210 (8.3)
ght	kg.(lb.)	1,480 (3,265)	1,575 (3,470)	1,590 (3,505)	1,720 (3,790)	1,800 (3,970)
Gross vehicle weight kg. (lb.)		2,050 (4,500)	2,050 (4,500)	2,300 (5,000)	2,900 (6,400)	2,600 (5,700)
Tyre size front		7.10-15, 4 P.R.		7.60-15, 4 P.R.	7.00-16, 6 P.R.	7.00-15, 6 P.R.
rear		7.10-15, 4 P.R.		7.60-15, 6 P.R.	7.00-16, 8 P.R.	7.00-15, 6 P.R.
m (ft.) 10.6 (35.0)		11.0 (36.0)	13.2 (43.0)	12.4 (41.0)		
	front rear length width height ce ght eight front	mm (in.) front mm (in.) rear mm (in.) length mm (in.) width mm (in.) height mm (in.) ce mm (in.) ght kg.(lb.) eight kg.(lb.) front rear	mm (in.) 2,285 front mm (in.) 1,404 rear mm (in.) 1,400 length mm (in.) 3,870 width mm (in.) 1,950 (76.8) rear mm (in.) 200 ght kg.(lb.) 1,480 (3,265) eight kg.(lb.) 2,050 (4,500) front rear 7.10-15 7.10-15 rear 7.10-15 rear r	Marcolons Marc	front mm (in.) 2,285 (90.0) 2,430 (95.7) front mm (in.) 1,404 (55.3) 1,404 (55.3) rear mm (in.) 1,400 (55.1) 1,400 (55.1) length mm (in.) 3,870 (152.4) 4,230 (166.5) width mm (in.) 1,665 (65.6) 1,665 (65.6) height mm (in.) 1,950 (76.8) 1,930 (76.0) 1,970 (77.6) ce mm (in.) 200 (7.9) 210 (8.3) ght kg. (lb.) 1,480 (3,265) 1,575 (3,470) 1,590 (3,505) eight kg. (lb.) 2,050 (4,500) 2,050 (4,500) 2,300 (5,000) front 7.10-15, 4 P.R. 7.60-15, 4 P.R. rear 7.10-15, 4 P.R. 7.60-15, 6 P.R.	front mm (in.) 2,285 (90.0) 2,430 (95.7) 2,950 (116.1) front mm (in.) 1,404 (55.3) 1,404 (55.3) 1,404 (55.3) rear mm (in.) 1,400 (55.1) 1,400 (55.1) 1,400 (55.1) length mm (in.) 3,870 (152.4) 4,230 (166.5) 4,985 (196.3) width mm (in.) 1,665 (65.6) 1,665 (65.6) 1,690 (66.5) height mm (in.) 1,950 (76.8) 1,930 (76.0) 1,970 (77.6) 1,960 (77.2) ce mm (in.) 200 (7.9) 210 (8.3) 230 (9.1) ght kg. (lb.) 1,480 (3,265) 1,575 (3,470) 1,590 (3,505) 1,720 (3,790) eight kg. (lb.) 2,050 (4,500) 2,050 (4,500) 2,300 (5,000) 2,900 (6,400) front 7,10-15, 4 P.R. 7,60-15, 6 P.R. 7,00-16, 8 P.R.

The right is reserved to alter prices and any details of specifications and equipment without notice. Details of specifications and equipment are subject to change to suit local conditions and requirements

Importeur voor Nederland

LOUWMAN & PARQUI

Veursestraatweg 280 - Tel. 01761 - 6911 LEIDSCHENDAM